

Series H & BT

.652", 16.56mm Center-to-Center Spacing

Current Rating: CSA & UL: H: 75 amps BT: 30 amps

Voltage Rating: CSA: 600V
UL: 600V General Industrial

Breakdown Voltage:	BT	H
Terminal - Terminal	10,400V Typ.	8,100V Typ.
Terminal - Ground	8,400V Typ.	7,600V Typ.

UL® Recognized under the Components Program of Underwriters Laboratories, Inc. Standard 1059, Guide No. XCFR2, File No. E62557.

SP® Guide No. 22.2 No. 158, Report No. LR39186-1.

No. of Terminals: 1 through 30

Wire Range:


H: UL Recognized for 16AWG to No. 4AWG
BT: UL Recognized for 22AWG to No. 10AWG

Tightening Torque:


H: 45 in.-lb. (4WG to 6AWG)
40 in.-lb. (8AWG)
35 in.-lb. (10AWG to 16AWG)
BT: 20 in.- lbs.

Housing:

Material	Thermoplastic-Polyester
Continuous Use	
Temp. (UL Index)	130°C (266°F)
Flammability Rating	UL 94V-0



TYPE H




TYPE BT


Features:

- **Sectional, High and Medium Power Terminal Blocks** – Designed for high power applications and control/power circuits respectively. Units approach power ratings of larger terminal blocks while retaining increased circuit density of low power designs.
- **Broad Terminal Choice** – One through 30 terminals on .652" center-to-center spacing with white fiber circuit marking strips.
- **Unique Bar and Traveling Collar Design** – Eliminates lugging of wire on Type H. UL recognized for No. 16AWG to No. 4AWG. Type BT uses two No. 10-32 terminal screws, UL recognized for No. 22AWG to No. 10AWG.
- **Combined Style Flexibility** – Types can be used in combination as well as be combined with types L, O, S, T & U for greater application flexibility.
- **Recognition and Listing** – UL recognized and CSA certified

Mechanical Drawing



Types H & BT Terminal Variations



Number of Terminals	Mounting Dimensions		Overall Dimensions	
	Inches	Metric (mm)	Inches	Metric (mm)
1	1.66	42.1	2.36	59.8
2	2.31	58.6	3.01	76.4
3	2.96	75.1	3.66	92.9
4	3.61	91.6	4.31	109.4
5	4.26	108.1	4.96	126.0
6	4.91	124.6	5.61	142.5
7	5.56	141.1	6.26	159.1
8	6.21	157.6	6.92	175.6
9	6.86	174.1	7.57	192.2
10	7.51	190.6	8.22	208.7
11	8.16	207.1	8.87	225.3
12	8.81	223.6	9.52	241.8
13	9.46	240.2	10.17	258.4
14	10.10	256.6	10.82	274.9
15	10.75	273.2	11.48	291.5
16	11.40	289.7	12.13	308.0
17	12.05	306.2	12.78	324.6
18	12.70	322.7	13.43	341.1
19	13.35	339.2	14.08	357.7
20	14.00	355.7	14.73	374.2
21	14.65	372.2	15.39	390.8
22	15.30	388.7	16.04	407.3
23	15.95	405.2	16.69	423.9
24	16.60	421.7	17.34	440.4
25	17.25	438.2	17.99	457.0
26	17.40	454.7	18.64	473.5
27	18.55	471.2	19.29	490.1
28	19.20	487.7	19.95	506.6
29	19.85	504.2	20.60	523.2
30	20.50	520.7	21.25	539.7

Part Number

How to Order

Types H and BT terminal blocks are ordered by listing a model number made up of the model designation followed by the number of terminals required for the application.
Example: a 10-pole terminal block becomes H-10 or BT-10
When ordering combinations of both types, the model number is made up of both model designations followed by total number of poles and number of each type. A composite of three H terminals followed by two BT terminals thus is converted to stock number HBT-5 (3H, 2BT).

Series H & BT Accessories

COVERS

Series H & BT – Plain cover of 1/16" thick black bakelite is fastened to the block with two screws. Factory-assembled or customer-installed.
To order, specify:
H/BT (Plain) – Part No. 260A49 – 1 through 30 terminals (0806850XX)